

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
8 June 2006 (08.06.2006)

PCT

(10) International Publication Number  
**WO 2006/059518 A1**

(51) International Patent Classification:  
**G03G 15/20** (2006.01)

(21) International Application Number:  
PCT/JP2005/021494

(22) International Filing Date:  
17 November 2005 (17.11.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
2004-347677 30 November 2004 (30.11.2004) JP

(71) Applicant (for all designated States except US): **RICOH COMPANY, LTD.** [JP/JP]; 3-6, Nakamagome 1-chome, Ohta-ku, Tokyo, 1438555 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **SATOH, Masahiko** [JP/JP]; 23-1-903, Fujiwara 6-chome, Funabashi-shi, Chiba, 2730047 (JP). **IWAYA, Naoki** [JP/JP]; 1-11-208, Shimokodanaka 4-chome, Nakahara-ku, Kawasaki-shi, Kanagawa, 2110041 (JP).

(74) Agent: **ITOH, Tadahiko**; 32nd Floor, Yebisu Garden Place Tower, 20-3, Ebisu 4-chome, Shibuya-ku, Tokyo 1506032 (JP).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KM, KN, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: FIXING DEVICE AND IMAGE FORMING APPARATUS USING THE SAME



(57) Abstract: A fixing device includes i) two surface moving bodies, at least one of which is driven so that the surface moving bodies come in contact with each other, a nip is formed, and surfaces of the surface moving bodies in contact move in the same direction, and ii) a heat source configured to heat at least one of the surface moving bodies. A transfer medium having a surface where a non-fixed toner image is formed is put in the nip so that the toner image is heat-fixed on the transfer medium. The fixing device further comprises a separation plate configured to remove the transfer medium, the transfer medium not being separated from the surface moving body after the transfer medium passes through the nip, from the surface moving body. Rise of temperature of a head end part, at a side of the surface moving body, of the separation plate is given priority over rise of temperature of other parts of the separation plate.

WO 2006/059518 A1



---

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*